## **EZ-Out** Solar Charger Quick Start Guide

### What's in the Pack





Frame

Carry/Storage

**EZ-Out Collapsible** 

**EZ-Out Tent** Pole



**EZ-Out Solar** Panel



**EZ-Out Frame** Stakes



**EZ-Out Packing** Tube





8 ft SAE **Extension Cable** 

#### the EZ-Out Frame How to set up

Baa



Remove all contents from the bag



Open the frame by moving the center struts toward each other



Stake the two front legs



Stake the two back straps



Stake the center strap forward

Step 1 & 2: First, remove all the contents from the EZ-Out Solar System bag. Expand collapsible frame by Step 3: Using a hammer, secure frame to ground with the 5 ground stakes provided. Center strap is staked forward to provide panel support. moving the center struts toward each other until you hear the snap buttons click into the side's holes.

#### the Rollable Pane



Hook solar panel Velcro to frame

Unroll solar panel and hook to Velcro on other side of the frame

Step 4: Hook panel's exposed Velcro flap to frame. Unroll solar panel and secure other side Velcro flap over opposite frame corner.




Insert tent pole into the pocket on one end of the solar panel



Insert tent pole into the pocket on the other end of the solar panel

Step 5: Connect collapsed poles to form one piece. Insert one end of the tent pole into the pocket on one of the bottom ends of the solar panel. Insert the other end of the tent pole into the pocket on the opposite side of the bottom end of the solar panel. Maneuver the tent pole so it slides behind the solar panel securing the lower half.



Insert tent pole into the pocket on the other end of the solar panel

Step 6: There are four cinch straps located on the solar panel, two on each side. One side, loop the cinch straps behind frame struts and wrap around ring. Pull panel to frame edge and secure Velcro cinch. Perform the same on the other side and frame leg.

# **EZ-Out** Solar Charger Quick Start Guide

### How to Connect the SAE 8 ft. Extension Cable



#### SAE cable connected to solar panel and load

 Connect one end of the SAE 8' extension cable to the solar panel junction box which is located on one end underneath the panel. Connect the other end of the SAE 8' extension cable to the battery adapter or load.



How to Dissassemble the EZ-Out Solar System



- Unplug SAE power cord from the solar panel and load and store in bag pocket.
- Remove panel cinch straps from both sides
  of the EZ-Out frame.
- Reach under solar panel and remove the poles and collapse and store in bag.
- Remove Velcro flap from one corner and roll panel, see above.



Wrap solar panel around the packaging tube



Slide solar panel and tube in bag



Store stakes in bag pocket



Collapse frame

Depress button snaps at sides of frame and collapse frame by pulling center struts apart.

Slide collapsed frame into tube and bag and pull cinch cord and secure lock